







Engineered with design simplicity in mind, Panasonic's RF Modules provide a superior developer experience and shortens time to market due to the quick implementation of Bluetooth® communication. Bluetooth® Modules by Panasonic deliver best-in-class power efficiency and enable any application requiring long battery life.

	Bluetooth® Low Energy				Bluetooth® Dual Mode	
						
Series	PAN1720 / PAN1721	PAN1740	PAN1760A	PAN1762	PAN1026A	PAN1326B/C
Status	Mass Production	Mass Production	Mass Production	Mass Production	Mass Production	Mass Production
Part Number	ENW898xxxxKF*	ENW89846A1KF	ENW89847A3KF	ENW89853A1KF	ENW89837A5KF	ENW89823x4KF*
RF Category	Bluetooth® Low Energy v4.0	Bluetooth® Low Energy v4.2	Bluetooth® Low Energy v4.2	Bluetooth® Low Energy v5.0	Bluetooth® v4.2 Dual Mode (BR, LE)	Bluetooth® v4.1/v4.2 Dual Mode (BR, EDR, LE)
Software / Profile	nBlue™ by BlueRadios Inc. / TI SW stack	Embedded Profiles	Embedded Profiles / AT-Command Mode	Embedded Profiles	SPP and GATT	HCI
Used ICs	CC2540 / CC2541	DA14580	TC35678	TC35680	TC35661-551	CC2564C
Size [mm]	15.6 x 8.7 x 1.8	9.0 x 9.5 x 1.8	15.6 x 8.7 x 1.9	15.6 x 8.7 x 1.9	15.6 x 8.7 x 1.8	9.0 x 9.5 x 1.8
Rx Sensitivity [dBm]	-94	-93	-93	-105 @ 125 kb/s	-89	-93
Tx Power (max.) [dBm]	+4 / 0	+0	+0	+8	+4	+10 / +12
Power Supply [V]	2.0 to 3.6	2.35 to 3.3	1.8 to 3.6	1.9 to 3.6	2.8 to 3.6	1.8 to 4.8
Current Consumption (max.)	Tx: 23mA @ -6dBm Rx: 18mA Sleep Mode: <1µA	Tx: 4.9mA Rx: 4.9mA Sleep Mode: <1µA	Tx: 3.3mA Rx: 3.3mA Deep Sleep Mode: 50nA	Tx: 11mA Rx: 5.1mA Deep Sleep Mode: 50nA	ACL, DH1: 46mA Sleep Mode: <2mA	Tx, EDR: 40mA Sleep Mode: 135µA
Interfaces	GPIO, UART, PAN1720: USB; PAN1721: I²C	GPIO, UART, SPI, I²C, 3-axis QD, ADC	GPIO, UART, SPI, I²C, ADC	SPI, I²C, UART, PWM, Wake-Up inputs, ADC, GPIO	GPIO, UART	GPIO, PCM, UART
Microcontroller and Memory	8051 µC 8KB RAM, 256KB Flash	ARM® Cortex®-M0 42KB SRAM, 32 KB OTP	ARM® Cortex®-M0 83KB RAM, 256KB Flash	ARM® Cortex®-M0 51KB RAM, 128KB Flash	ARM 7	
Operating Temp. [°C]	-40 to +85	-40 to +85	-40 to +85	-40 to +85	-40 to +85	-40 to +85
Evaluation Kit	ENW89820AYxF (PAN1720 Dongle Kit) ENW89835AY1F (PAN1721 Dongle Kit)	ENW89846AYKF (Dongle Kit) ENW89846AVKF (EMK)	ENW89847AWKF (Dongle Kit)	ENW89853AWKF (Dongle Kit)	ENW89837AUKEF (Dongle Kit) ENW89837AWKF (EMK)	ENW89819AYKF (EMK)

Panasonic Industry Europe GmbH  
[industry.panasonic.eu](http://industry.panasonic.eu)  
[wireless.connectivity@eu.panasonic.com](mailto:wireless.connectivity@eu.panasonic.com)

Status of engineering sample (ES) are expected as of the time of leaflet production.  
 The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Panasonic is under license. Other trademarks and trade names are those of their respective owners.

- Design and specification are subject to change without notice.
- Ask Panasonic for technical specification before purchase and/or use.
- If there is any doubt regarding the safety of this product, kindly inform Panasonic immediately for technical consultation.
- Same color indicates same form factor and compatible pinout for major functions.

- Qualification of all products: CE, FCC, IC, Bluetooth® QDID if applicable.
- Different software/profile options available.
- Non antenna version for some modules available.

\* x is a parameter to be defined.

Long life, reliability and excellent performance – Panasonic offers *Bluetooth*® Low Energy in combination with all important short range RF technologies: WiFi® (2.4GHz & 5GHz), IEEE 802.15.4 or NFC

	NFC + BLE	IEEE 802.15.4 + BLE	Wi-Fi® + BLE	Wi-Fi®	
<b>Series</b>	PAN1761	PAN4620	PAN9026	PAN9010/PAN9020	PAN9420
<b>Status</b>	Mass Production	Pre-Production	Mass Production	Mass Production	Mass Production
<b>Part Number</b>	ENW89848A1KF	ENWC9B01A1EF	ENWF9202A1EF (EU) ENWF9201A1EF (US) ENWF9203A1EF (CA)	ENW49801A1JF (Antenna) ENW49801C1JF (Non-antenna)	ENW49C02A6KF (EU) ENW49C01A6KF (US/CA)
<b>RF Category</b>	<i>Bluetooth</i> ® Low Energy v4.1 + NFC Tag Type 3	IEEE® 802.15.4 + <i>Bluetooth</i> ® Low Energy v4.2	Wi-Fi® Radio 2.4 GHz & 5 GHz 802.11 a/b/g/n + <i>Bluetooth</i> ® 5.0 (BR, EDR, LE)	Wi-Fi® Radio 802.11 b/g/n	Wi-Fi® Embedded 802.11 b/g/n
<b>Software / Profile</b>	Embedded Profiles	NXP's <i>Bluetooth</i> ®, Thread & ZigBee Stack	Linux	Linux / Android Driver	Full Embedded
<b>Used ICs</b>	TC35670-006	KW41Z	88W8977	88W8782	88MW300
<b>Size [mm]</b>	15.6 x 8.7 x 1.8	15.6 x 8.7 x 1.9	17.5 x 10.0 x 2.6	22.75 x 13.5 x 2.42	29.0 x 13.5 x 2.66
<b>Rx Sensitivity [dBm]</b>	-90	-93	-98 @ 1M-DSSS	-98 @ 1M-DSSS	-97 @ 1M-DSSS
<b>Tx Power (max.) [dBm]</b>	+0	+3	+17 @ 11b	+18 @ 11b	+16 @ 11b
<b>Power Supply [V]</b>	1.8 to 3.6	1.8 to 4.2	1.8 to 3.3	3.0 to 3.6	3.0 to 3.6
<b>Current Consumption (max.)</b>	Tx: 5.5mA Rx: 5.5mA Sleep Mode: <0.1µA	Tx: 7.6mA Rx: 8.5mA Low Power Mode: 182nA	Tx: 400mA @ 11Mbps Rx: 70mA @ 11Mbps Power Down Mode: 150µA	Tx: 400mA @ 11Mbps Rx: 105mA @ 11Mbps Power Down Mode: 200µA	Tx: 310mA @ 11Mbps Rx: 75mA @ 11Mbps Power Down Mode: <1mA
<b>Interfaces</b>	GPIO, UART, I²C, NFC Wake-Up, etc.	UART, SPI, I²C, TSI, ADC & DAC	SDIO 3.0, HS UART	USB 2.0	2x UART, SPI
<b>Microcontroller and Memory</b>	64KB EEPROM, 1.5KB EEPROM NFC memory	ARM® Cortex®-M0+ 128KB SRAM, 512KB Flash			2MB Flash
<b>Operating Temp. [°C]</b>	-30 to +85	-40 to +85	-30 to +85	0 to +70	-40 to +85
<b>Evaluation Kit</b>	ENW89848AVKF (EMK)	ENWC9B01AQEF (Daughter Board)	ENWF9201AXEF (i.MX) ENWF9201AYEF (Dongle Kit)	ENW49802AYJF (KIT)	ENW49C01AYKF (EMK) ENW49C01AXKF (Arduino Shield)

Panasonic Industry Europe GmbH  
[industry.panasonic.eu](http://industry.panasonic.eu)  
[wireless.connectivity@eu.panasonic.com](mailto:wireless.connectivity@eu.panasonic.com)

Status of engineering sample (ES) are expected as of the time of leaflet production.  
 The *Bluetooth*® word mark and logos are registered trademarks owned by *Bluetooth* SIG, Inc. and any use of such marks by Panasonic is under license. Other trademarks and trade names are those of their respective owners.